

## HIGH SPEED AUTOMATIC STRAPPING MACHINES

- High speed automatic strapping machine can make 1.1 second/strap
- German Dunker DC motor
- Manual and auto mode operation
- Loop ejecting function and refeed function
- Rigid structure design
- Built for 24 hours continuous operation
- Tension adjustment: very easy from control panel
- PCB+LCD screen: visualize temperature and banding tension
- Banding count function
- Easy strep loading and unloading
- Can be used for 5mm strap.save your cost

### Specifications

MODEL	Q80K
Motor	China VTV DC
Strap	P P Strap
Strap Specification	Width 5 /9/12mm, Thickness – 0.35-0.65 mm
Arch Size	W400 X H320 mm
Strapping Size	Max : W400 X H270, Min : W 100 X H50m
Power	220v 50hz , 500w
Control Systems	Pcb (PLC is possible)
Strapping Speed	1.5 sec/strap
Tension	10-400n
Table Height	750-800mm
Welding Method	Heat Sealing



MODEL : Q80K



MODEL : Q80D

- High Speed Automatic Strapping Machine Upto 50 Straps/minute.
- Manual And Auto Mode Operation.
- Loop Ejecting Function And Refeed Function With Rigid Structure Design.
- Built For 24 Hours Continuous Operation.
- Easy Tension Adjustment From Control Panel.
- Easy Strap Loading And Unloading (Dispenser Inside Machine).
- 5mm Strap Saves Consumable Cost.
- Uses China DUNKER Brand Motor DC24 Volts.

### Specifications

MODEL NO.	Q80D
Strapping tension	2-40 Kg
Strapping speed	50 Straps/Minute
Strap width	5/6mm, 7mm, 8 to 12mm
Strap thickness	0.45mm to 0.80mm
Strap roll diameter	ID = 200mm, OD = 420mm, W = 190mm
Table height	750 mm
Min package size	70mm (W) x 20mm (H)
Arch Size	1250mm (W) x 400mm (H)
Control System	PCB
Net weight	200KG
Power supply	220V, 50Hz
Power	850W

- High Speed Automatic Strapping Machine Upto 26 Straps/minute
- Manual And Auto Mode Operation
- Loop Ejecting Function And Refeed Function With Rigid Structure Design
- Built For 24 Hours Continuous Operation
- Easy Tension Adjustment : From Control Panel
- PLC+ Touch Screen Control System
- 5mm Strap Saves Consumable Cost.
- Uses China DUNKER Brand Motor DC24 Volts.
- Multiple Strap Function For Single or Double Strapping.
- Especially Designed For Corrugated, Print And Newspaper Industry.
- Full Width Soft Compression System.
- Variable Conveyor Speed
- Light Tree Alarm and Low Strap Sensor.
- Strap Cycle Counter to Track Consumable Cost.

### Specifications

Model No.	Q80DAP
Strapping tension	5-30 Kg
Strapping speed	16 Bundle / Minute (with compression)
Strap width	5/6mm, 7mm, 8 to 12mm
Strapping thickness	0.35mm to 0.65mma
Strap roll diameter	ID = 200mm, OD = 420mm, W = 190mm
Table height (Adjustable)	830mm to 930mm
Min package size	70mm (W) x 20mm (H)
Arch Size	1250mm (W) x 500mm (H)
Power supply	220V, 50Hz
Power	850W
Working noise	78dBA
Ambient temperature	5° – 40 °C
Control System	PLC
Net weight	480KG
Cylinder Stroke	40 x 500 mm
Machine Size	1680 x 705 x 2100 mm
Air Supply	0.5-0.6mPa



MODEL : Q80DAP



MODEL : Q80DAP + XT-AF01

## ALLESPACK SYSTEMS PVT. LTD.

FLAT NO. 7, 3RD FLOOR, 18A/26, WARD NO. 1. MEHRAULI, NEW DELHI - 110030

PHONE : 011-26642064 MOB. : 9868175404, 9015997050, 9868522553

E-MAIL : [allespack@gmail.com](mailto:allespack@gmail.com) WEBSITE : [www.allespack.com](http://www.allespack.com)