

## HIGH SPEED AUTOMATIC STRAPPING MACHINES

- High speed automatic strapping machine can make 1.1 second/strap
- German Dunker DC motor
- Manual and auto mode operation
- Loop ejecting function and refeed function
- Rigid structure design
- Built for 24 hours continuous operation
- Tension adjustment: very easy from control panel
- PCB+LCD screen: visualize temperature and banding tension
- Banding count function
- Easy strep loading and unloading
- Can be used for 5mm strap.save your cost

### Specifications

|                     |   |
|---------------------|---|
| <b>MODEL</b>        | <b>Q80K</b>                               |
| Motor               | China VTV DC                              |
| Strap               | P P Strap                                 |
| Strap Specification | Width 5 /9/12mm, Thickness – 0.35-0.65 mm |
| Arch Size           | W400 X H320 mm                            |
| Strapping Size      | Max : W400 X H270, Min : W 100 X H50m     |
| Power               | 220v 50hz , 500w                          |
| Control Systems     | Pcb (PLC is possible)                     |
| Strapping Speed     | 1.5 sec/strap                             |
| Tension             | 10-400n                                   |
| Table Height        | 750-800mm                                 |
| Welding Method      | Heat Sealing                              |



**MODEL : Q80K**

### Specifications

|                     |                                   |
|---------------------|-----------------------------------|
| <b>MODEL NO.</b>    | <b>Q80D</b>                       |
| Strapping tension   | 2-40 Kg                           |
| Strapping speed     | 50 Straps/ Minute                 |
| Strap width         | 5/6mm, 7mm, 8 to 12mm             |
| Strap thickness     | 0.45mm to 0.80mm                  |
| Strap roll diameter | ID = 200mm, OD = 420mm, W = 190mm |
| Table height        | 750 mm                            |
| Min package size    | 70mm (W) x 20mm (H)               |
| Arch Size           | 1250mm (W) x 400mm (H)            |
| Control System      | PCB                               |
| Net weight          | 200KG                             |
| Power supply        | 220V, 50Hz                        |
| Power               | 850W                              |



**MODEL : Q80D**

- High Speed Automatic Strapping Machine Upto 50 Straps/minute.
- Manual And Auto Mode Operation.
- Loop Ejecting Function And Refeed Function With Rigid Structure Design.
- Built For 24 Hours Continuous Operation.
- Easy Tension Adjustment From Control Panel.
- Easy Strap Loading And Unloading (Dispenser Inside Machine).
- 5mm Strap Saves Consumable Cost.
- Uses China DUNKER Brand Motor DC24 Volts.

- High Speed Automatic Strapping Machine Upto 26 Straps/minute
- Manual And Auto Mode Operation
- Loop Ejecting Function And Refeed Function With Rigid Structure Design
- Built For 24 Hours Continuous Operation
- Easy Tension Adjustment : From Control Panel
- PLC+ Touch Screen Control System
- 5mm Strap Saves Consumable Cost.
- Uses China DUNKER Brand Motor DC24 Volts.
- Multiple Strap Function For Single or Double Strapping.
- Especially Designed For Corrugated, Print And Newspaper Industry.
- Full Width Soft Compression System.
- Variable Conveyor Speed
- Light Tree Alarm and Low Strap Sensor.
- Strap Cycle Counter to Track Consumable Cost.

### Specifications

|                           |                                       |
|---------------------------|---------------------------------------|
| <b>Model No.</b>          | <b>Q80DAP</b>                         |
| Strapping tension         | 5-30 Kg                               |
| Strapping speed           | 16 Bundle / Minute (with compression) |
| Strap width               | 5/6mm, 7mm, 8 to 12mm                 |
| Strapping thickness       | 0.35mm to 0.65mma                     |
| Strap roll diameter       | ID = 200mm, OD = 420mm, W = 190mm     |
| Table height (Adjustable) | 830mm to 930mm                        |
| Min package size          | 70mm (W) x 20mm (H)                   |
| Arch Size                 | 1250mm (W) x 500mm (H)                |
| Power supply              | 220V, 50Hz                            |
| Power                     | 850W                                  |
| Working noise             | 78dBA                                 |
| Ambient temperature       | 5° – 40 °C                            |
| Control System            | PLC                                   |
| Net weight                | 480KG                                 |
| Cylinder Stroke           | 40 x 500 mm                           |
| Machine Size              | 1680 x 705 x 2100 mm                  |
| Air Supply                | 0.5-0.6mPa                            |



**MODEL : Q80DAP**



**MODEL : Q80DAP + XT-AF01**

## ALLESPACK SYSTEMS PVT. LTD.

FLAT NO. 7, 3RD FLOOR, 18A/26, WARD NO. 1. MEHRAULI, NEW DELHI - 110030

PHONE : 011-26642064 MOB. : 9868175404, 9015997050, 9868522553

E-MAIL : [allespack@gmail.com](mailto:allespack@gmail.com) WEBSITE : [www.allespack.com](http://www.allespack.com)