

## SEMI AUTOMATIC STRAPPING MACHINES



**MODEL : 405P XUTIAN**

- 5 seconds to enter into working status.
- 1v low voltage.
- 60 seconds stand by time.
- Rigid mechanical parts.
- Tension detector or Round Belt.
- Heater Temperature control.

### Specifications

<b>Model</b>	<b>405P</b>
Max Packaging Size	Any Size
Min Packaging Size	60mm
Strap Width	6-15mm
Strap Core Size	200mm
Strapping Tension	15-50kgs
Strapping Speed	1.5 sec/strap
Power Consumption	400W
Power Supply	AC 220 V (50hz)
Dimensions	895(L)x565(W)x730(H)mm
NetWeight	100kg



**MODEL : 405 XUTIAN**



**MODEL : JN-740 CHALI**

- Instant heating in 20 seconds.
- Economical design of control switch, independent PCB controls feeding, tensioning and heating.
- Energy saving mode activates within 15 seconds of non-use and allows for instant operation.
- Innovatory die-cast seal blade eliminates blade distortion, short circuiting and rapid aging that are common in many conventional strapping machines.
- Easier changeover of straps suitable for 6~15mm strap width through strap guide.

### Specifications

<b>Model</b>	<b>JN-740</b>
Strap Cycle Speed	1.5 sec./cycle
Tension Strength	15~60kgs
Table Height	735mm
Strap Width	6~15mm
Sealing Method	Heat Sealing
Power Supply	110/220V 50/60Hz single phase
Dimensions	895W x 570D x 735H mm
Machine Weight	92.5kgs
Gross Weight	107kgs

- Suitable for continuous application area like Airports, Tiles, Meat units, Newspaper Bundling etc.
- "Electricity-saving" device, the motor automatically stops running after 60 seconds.
- High engineering standard and simple design
- Easy operation, simple maintenance
- Hinged stainless steel top plate
- Mechanical outside tension control
- Rigid castors with brake
- Reliable P.C. Board control

### Specifications

<b>Model</b>	<b>TP201</b>
Max Packaging Size	Any Size
Min Packaging Size	20(H)x80(W)
Strap Core Inner Dia	200mm
Strap Width	6 ~ 15mm (adjustable)
Strap Thickness	0.5 ~ 0.75mm
Strapping Tension	15-45 kg (Max)
Table Height	775mm
Max Package Weight	100kg
Strapping Speed	2.5 Sec/Cycle
Power Consumption	0.25 KW
Power Supply	AC 220 V (50/60hz) 1PH
Dimensions	586(D)x902(W)x775(H)mm
Net Weight	100kg



**MODEL : TP201 TRANSPAK**



**MODEL : 207 PACKWAY**



**MODEL : 207L/405L/202L**

- Low Height Floor Model
- Suitable for heavy cartons and articles like tyres, bales etc.
- Option of ball bearing top for easy movement of product.

### Specifications

<b>Model</b>	<b>207</b>
Max Packaging Size	Any Size
Min Packaging Size	60mm
Strap Width	6-15mm(adjustable)
Strap Core Size	200mm
Strapping Tension	15-50kgs
Strapping Speed	1.5 sec/strap
Power Consumption	400W
Power Supply	AC 220 V (50/60hz)
Dimensions	910(L)x580(W)x750(H)mm
Net Weight	97kg
Gross Weight	108kg

## ALLESPACK SYSTEMS PVT. LTD.

FLAT NO. 7, 3RD FLOOR, 18A/26, WARD NO. 1. MEHRAULI, NEW DELHI - 110030

PHONE : 011-26642064 MOB. : 9868175404, 9015997050, 9868522553

E-MAIL : [allespack@gmail.com](mailto:allespack@gmail.com) WEBSITE : [www.allespack.com](http://www.allespack.com)