

SHRINK WRAPPING MACHINES

SHRINK TUNNELS



MODEL : 4525

- Adopts hot air with down cyclone pressure structure.
- Intelligent temperature control and AC variable speed regulator.
- Both the height of tunnel and shutters on two sides are adjustable.
- Adopts single/double hot air blower.
- Can be used with heat shrinkable film such as PVC, POF, P.E. etc.
- OPTIONAL : Teflon Belt conveyor for small products is available.

Specifications

Model	Voltage	Power	Conveyor Loading	Heating Chamber Size (mm)	Speed (m/min)	Net Wt(kg)	Dimension (LXWXH)mm
2615	220V	3.5 KW	10 KG	L260xH150	0-6	35	1200x540x660
4525	220V/380V	6.5KW	15KG	900x450x(50-250)	0-10	75	1200x610x1240
4535L	380V-3PH	9.6KW	30KG	1200x450x(50-350)	0-10	120	1600x610x1340
6535L	380V3PH	9.6KW	30KG	1200x650x(50-350)	0-10	150	1600x850x1200
5540M-PE	380V3PH	21KW	40KG	1400x550x400	0-10	280	2470x710x1450

SHRINK CHAMBER

- One operation
- Uses soft POF film
- Low energy consumption
- Wraps single and multipacks
- Visual observation possible
- Easy to work with one operator

Specifications

Max Packing Dimension (LxWxH)(mm)	450x300x250
Running Load(kw/hr)	1.9 kw
Power Consumption	3.5 kw
Power Supply	AC 220V/50HZ
Dimensions(LxWxH)(mm)	1895x720x1080mm
Net Weight(kg)	110kg



MODEL : SC1520

L SEALERS

MANUAL L SEALER



MODEL : LS1520

- Can wrap the products for shrink packaging after sealing & cutting.
- Sealing and Cutting time can be controlled by time relay accurately.

- Conveys products automatically into shrink tunnel.
- Upper sealing and cutting frame is Lowered Manually by operator.
- Post sealing conveyor feeds product into tunnel.

Specifications

Max Packing Dimension (LxWxH)(mm)	450x400x250
Max Sealing Dimension(mm)	500x450
Power Consumption(KW)	1.0
Power Supply	AC 220V/50HZ
Dimensions(LxWxH)(mm)	1560x700x1100
Net Weight(kg)	60 Approx

Specifications

Max Packing Size (LxWxH)(mm)	450x400x300
Speed	800-1200
Power Consumption(kw)	1.2
Power Supply	220v/50Hz 1 ph
Dimensions(LxWxH)(mm)	1560x757x1040mm
Net Weight(kg)	125



MODEL : 5045L

SEMI AUTO L SEALER

FOOT SEALER MACHINES

Specifications

Model	Description	Sealing Width(mm)	Sealing Length(inch)	Power Consumption (Watts)
FSI-12	Impulse Sealer	3	12	350
FSH-24	Hot Bar Sealer	12	24	1000

- For sealing poly pouches and bags
- High quality double transformer in Copper Winding
- Our Hot bar elements are made from BRASS
- Adjustable electronic timer
- Audio visual sealing alarm
- Hot Bar Sealer are suitable for multi layer laminates of Aluminium / Paper / Polyurethane



HAND SEALER MACHINES

- High quality double transformer
- Brass Hot bar elements
- Adjustable electronic timer
- Audio and visual
- Hot Bar Sealer for Multilayer Laminated pouches
- Round element Impulse sealers for sealing + cutting.



Specifications

Model	Description	Sealing Width(mm)	Sealing Length(inch)	Power Consumption (Watts)
FSI-12	Impulse Sealer	1.6	12	300
FSH-12	Hot Bar Sealer	12	12	300

ALLESPACK SYSTEMS PVT. LTD.

FLAT NO. 7, 3RD FLOOR, 18A/26, WARD NO. 1. MEHRAULI, NEW DELHI - 110030
 PHONE : 011-26642064, 26644625 MOB. : 9868175404, 9868522553, 9211771113, 9015997050
 E-MAIL : allespack@gmail.com WEBSITE : www.allespack.com